

Bolt Down Round Aluminum Fluted Poles

Project: _





MOUNTING DETAIL Various heights and fixture

configurations may require a different bolt circle. Consult factory for specific bolt circle required.

Material

Aluminum pole bases and base plates shall be cast from 356 aluminum alloy. Shafts shall be extruded 6061-T6 aluminum. Available in 3", 4" or 5" diameter. Wall thickness 0.125" or 0.188" or 0.250.

Mounting

Four anchor bolts provided are ³/₄"x18". Anchor bolts, nuts and washers are hot dipped galvanized steel. Spun aluminum bolt cover provided.

Access

All poles are provided with a hand access opening and cover. Hand hole cover is secured by two stainless steel machine screws. (Tamper-proof screws provided upon request).

Grounding

All poles are provided with an aluminum grounding lug integrated to inner wall of shaft, 180 degrees to hand hole. Grounding lug is drilled and tapped to accommodate ¼-20 stainless steel machine screw.

Pole Height

Maximum pole height is 16-feet.

Accessories

Banner arms, ladder rests, signage, flag pole holder and GFI receptacles are optional.

Finish

A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity, and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

		Гуре:	Quantity:			
	Custo	omer:	Made in USA		minating	
atalog Logic BD3	BF10.125 Pole	5 - BA Access		S1902 - Clamshell	5	
atalog Number		2)		3	4	
Item Number	OD	Height	Wall	80 MPH	100 MPH	
BD3F6.125	3.00"	6'	.125	6.60	3.80	
BD3F7.125	3.00"	7'	.125	5.90	3.30	
BD3F8.125	3.00"	8'	.125	5.30	3.00	
BD3F9.125	3.00"	9'	.125	4.60	2.50	
BD3F10.125	3.00"	10'	.125	3.90	2.00	
BD4F8.188	4.00"	8'	.188	16.00	7.30	
BD4F9.188	4.00"	9'	.188	14.40	6.60	
BD4F10.188	4.00"	10'	.188	12.80	5.90	
BD4F11.188	4.00"	11'	.188	11.50	5.10	
BD4F12.188	4.00"	12'	.188	10.50	4.50	
BD4F13.188	4.00"	13'	.188	7.90	3.50	
BD4F14.188	4.00"	14'	.188	5.10	2.50	
BD5F10.188	5.00"	10'	.188	17.00	10.70	
BD5F11.188	5.00"	11'	.188	15.50	9.60	
BD5F12.188	5.00"	12'	.188	14.00	8.50	
BD5F13.188	5.00"	13'	.188	12.60	7.70	
BD5F14.188	5.00"	14'	.188	11.20	7.00	
BD5F15.188	5.00"	15'	.188	10.00	6.30	
BD5F16.188	5.00"	16'	.188	8.90	5.60	

Bolt Down Round Aluminum Fluted Poles

Project: _

.....

Fixture Type: _____ Quantity: ____

Customer: ____

2 ACCESSORIES GFI15 (15 amp GFCI receptacle outlet) Ð GFI20 (20 amp GFCI receptacle outlet) GFI-WPU (20 amp GFCI receptacle with weather proof in-use cover) ваа (Cast Banner Arm A for 24" wide banner) вав (Cast Banner Arm B for 30" wide banner) CD-BAC (Cast Banner Arm C for 30" wide banner) (1)= LR1 (Cast Ladder Rest 1) LR3 (Cast Ladder Rest 3) O₽⊏ **4**0 LR4 (Cast Ladder Rest 4) -D-111 LR5 (Cast Ladder Rest 5) (Cast Sign A; 30" x 9", 8 letters/numbers on one line; requires Banner Arm to hang) SIGN A æ (TOUR SIGN) (Cast Sign B; 31" x 7", 12 letters/numbers on one line requires Banner Arm to hang) SIGN B (YOUR SICN) (Cast Sign C; 27" x 11", two rows of 8 letters/numbers on each line, requires Banner Arm to hang) SIGN C . 1 (Cast Sign D; 11" x 6 1/2", 4 letters/numbers on one line) SIGN D

0.0112	(ouse eight b, i		of fighter of the second se	•≈⊐p-	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
SIGN E	(Cast Sign E; c numbers on o	omes with pole cla ne line)	amp, 24 1/2"	x 6", 9 letters/		
FPH1	(Flag Pole Hol	der)	b	L LOOK SIGH	//	
ТР	(Tamper Proof	Screws)	\bigcirc			
BDC	(Spun Aluminun	n Bolt cover)	9			
SBDC	(Split Bolt Cove	er)	A)			
						1
3	2-P		ISHEL	LS		
CCS03	300	CCS1302		CCS2902		
CCS0	509	CCS1501		CCS2903		
CCS07	701	CCS1502		CCS5301		
CCS07	702	CCS1504		CCS5401		
CCS09	900	CCS1509		CCS5509		
CCS11	00	CCS1607		CCS6303		
CCS12	201 📇	CCS1608		CCS6502	\square	
CCS13	301 🗖	CCS1902		CCS9103		

4 *Premium a	nd Marine		ISHES Finish have additio	nal char	aes
Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade
Aspen Green	10	10M	Architectural Bronze	51	
Cantaloupe	11	11M	Patina Verde	52	52N
Lilac	12	12M	Copper Clay	53	53N
Putty	13	13M	Silver	56	56N
Raw Unfinished	40	NA	Black Verde	61	61N
Black	41	41M	Painted Chrome	70	70N
Forest Green	42	42M	Painted Copper	71	71N
Bright Red	43	43M	Textured Black	72	72N
White	44	44M	Matte Black	73	73N
Bright Blue	45	45M	Textured Architectural Bronze	76	76N
Sunny Yellow	46	46M	Textured White	77	77M
Aqua Green	47	47M	Textured Silver	78	78N
Galvanized	49	NA	PREMIUM FINISH	PREMIUM FINISH Grade*	
Navy	50	50M	Carbon Graphite	96	96M
			Wood Grain	99	NA