


Customer:

Project:

Fixture Type: _







Specifications

Material:

Shade is 0.80" spun aluminum. Cast Aluminum Hub and Wall Canopy

Electrical:

Medium Base Socket, 200w Max and 120v only.

Certifications:

Cord mounts are UL listed for dry locations. Arm mount are UL listed for wet locations.

Finish:

A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Quantity:


Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:

Consult factory for custom or modified designs.

EU822 200w Max Incandescent 22" Euro Barn

Weight: 5.7 lbs







	76	121	Architectural Bronze	
	77	127	Textured White	
	78	124	Textured Silver	
	10	130	Aspen Green	
	11	131	Cantaloupe	
	13	132	Putty	
	Premium Grade	Marine Grade		
me	64	116	Candy Apple Red	
ert	65	122	Cobalt Blue	
	82	128	Graystone	
	69	113	Gunmetal Gray	

WARRANTY

See www.ANPlighting.com for complete fixture warranty

2 MOUNTING				
Arm Mounts				
E31UR18				
E33UR22				
E35UR18				
Cord Mounts				
BLCUR (6' black cord, UR cast hub & 5 1/4" x 2 3/4" canopy)				
WHCUR (6' white cord, UR cast hub & 5 1/4" x 2 3/4" canopy)				
XXXXUR (6' color cord, UR cast hub & 5 1/4" x 2 3/4" canopy. Replace XXXX with color cord designation from page 3.)				

4	ACCESSORIES
GUP110	(Wire lamp guard)
GUP120	(Wire lamp guard)
TCPG	(Grey, braided cord cover)


Project:			
Fixture Type:	Quantity:		
Customer:			









PENDANT MOUNTS




EU822-BLCUR

ARM MOUNTS









EU822-E33UR22

EU822-E35UR18

ACCESSORIES





1-800-548-3227

Project: ______ Quantity: ______ Customer: _____

All fabric Color Cords are three conductor, 1/4" diameter





