

33.0 lbs

Weight: EPA: 2.81

Project: _ __ Quantity: _ Fixture Type: __

Specifications

Material:All parts are durable 356 cast aluminum. All hardware provided shall be stainless steel or zinc plated steel.

Customer:

Lens: Standard polycarbonate lens.

Fixture Mounting:
Post Mount: Post Cap with set screws.
Pendant Mount: Pin mount to tenon.
Fits 3" and 4" poles.

Medium Base Socket or GU24 Socket.

Approximately 12" of pull wire extends from luminaire. Additional pull wire provided for post mount arms and wall mounts.








Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Consult factory for custom or modified designs.

LA333 Medium Base





1	FIXTURE ORIENTATION
1 Post	
3 Pendant	
2	LENS

41	LENS
FR	(Frosted Acrylic)
PR	(Prismatic Acrylic)
SE	(Seeded Acrylic)
WH	(White Opal Acrylic)

3	FIXTURE ORIENTATION
МВ	(Medium Base Socket)
GU24	(GU24 Socket)

4	ACCESSORIES
HSS90	(90° House Side Shield, polished)
HSS120	(120° House Side Shield, polished)
**4ST36	(3 Ft, 1 1/4" Ridged Stem & Canopy)
**PEND-CH3	(3 Ft Pendant Chain & Canopy)
HLMSPC-06	(High-Low Motion Sensor/Photocell; 15' - 30' Sensor Mounting Height)
HLMSPC-10	(High-Low Motion Sensor/Photocell; 8' - 15' Sensor Mounting Height)
PC	(Button Photo Cell)
SP	(Surge Protector, 10kA & 10kV)
TLPC	(Twist Lock photo cell, includes receptacle & photo cell)
TL5	(5-pin Twist Lock receptacle)
TL7	(7-pin Twist Lock receptacle)
*For Emerg Resources se	ency lumen output data, see oction at <u>www.ANPlighting.com</u> .
**Accessory	finish will match fixture finish.

5		MOUNTIN	IG SOURC	E
Post Mount Arms *See Page 2 for Style/Size		Wall Mount Arms *See Page 2 for Style/Size		
PA3	111	PA8521	WM4511	WM8581
PA3	113	PA8523	WM4513	WM8583
PA5	151		WM5131	
PA5	153		WM5133	
PA5	411		WM5161	
PA5	413		WM5163	
PAG	211		WM5601	
PAG	213		WM5603	
PA8	031		WM6111	
PA8	033		WM6113	
Column Mount *See Page 2 for Style/Size				
СМ	Colur	nn Mount		

-Premit			e Finish have additional ch	_	
Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Mar
Aspen Green	10	10M	Architectural Bronze	51	51
Cantaloupe	11	11M	Patina Verde	52	52
Lilac	12	12M	Copper Clay	53	53
Putty	13	13M	Silver	56	56
Raw Unfinished	40	NA	Black Verde	61	61
Black	41	41M	Painted Chrome	70	70
Forest Green	42	42M	Painted Copper	71	71
Bright Red	43	43M	Textured Black	72	72
White	44	44M	Matte Black	73	73
Bright Blue	45	45M	Textured Architectural Bronze	76	76
Sunny Yellow	46	46M	Textured White	77	77
Aqua Green	47	47M	Textured Silver	78	78
Galvanized	49	NA	PREMIUM FINISH	Preminum Grade*	Mar Gra
Navy	50	50M	Carbon Graphite	96	96

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

*Limited Warranty: A typical year is defined as 4380 hours of operation.

Project: ___ Fixture Type: _____ Quantity: _____ Customer:

POST MOUNTS - See Post Arm Section on Website for Specification Sheets and additional post arms. Dimensions are Projection x Height

COLUMN MOUNT













PA6213 / 22 3/4" x 26 1/2"

CM / 5 3/4" SQ x 3 1/2" H

PA5411 / 17 7/8" x 25 1/8"



PA5413 / 17 7/8" x 25 1/8" PA8033 / 20 1/2" x 20 1/4"

PA6211 / 22 3/4" x 26 1/2" PA8521 / 18 1/4" x 14 1/2"





WALL MOUNTS - See Wall Mount Section on Website for Specification Sheets and additional wall mount arms. Dimensions are Projection x Height.

















WM6111 / 20 3/8" x 24"



WM5161 /15 3/4" x 13 3/4" WM8581 / 17 1/8" x 17 1/2"

ACCESSORIES













