

Project: _ Quantity: _ Fixture Type: ___

Customer: _





Weight: 34.0 lbs EPA: 1.7

Due to size or weight, arms mounts may not accommodate all ANP luminaires.

Specifications

Material: All parts are durable 356 cast aluminum and high strength extruded aluminum. All hardware provided shall be stainless steel or zinc plated

Fixture Mounting: Post Cup mount to tenon.

Post Arm Mounting: Post Cup to accomodate 3" and 4" pole. Pole section of arm matches pole diameter and style.

Electrical:

Pull wire provided.


A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating ov protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.


Modifications:Consult factory for custom or modified designs.

PA7421-2 - POST ARM

Cast aluminum post arm for post fixture.







1 POST ARM ORIENTATION	3 CENTER MOUNT OPTIONS			
1 - Post	N/A			
2 NUMBER OF ARMS	4 POLE DIAMETER			
	3 - 3 Inch			
2- Two Arm Configuration	4 - 4 Inch			
	5 POLE STYLE			
	S - Smooth			
	F - Fluted			

6	FINISHES						
Standard Grade	Marine Grade		Standard Grade	Marine Grade			
40	NA	Raw Unfinished	53	100	Copper Clay		
41	101	Black	56	109	Silver		
42	102	Forest Green	61	106	Black Verde		
43	114	Bright Red	70	118	Painted Chrome		
44	107	White	71	105	Painted Copper		
45	112	Bright Blue	72	108	Textured Black		
46	123	Sunny Yellow	73	125	Matte Black		
47	120	Aqua Green	76	121	Textured Architectural Bronze		
49	NA	Galvanized	77	127	Textured White		
50	111	Navy	78	124	Textured Silver		
51	103	Architectural Bronze	10	130	Aspen Green		
52	104	Patina Verde	11	131	Cantaloupe		
12	133	Lilac	13	132	Putty		
Consult factory for additional paint charges and availability							