ANP Lighting
INNOVATIVE SITE LIGHTING

Specifications VTP100GL-CL-32WPL-RTC-BLC-GUPC

			Project:		
			Fixture Type:		Quantity:
			Customer:		
					ade in USA
		← 4 1/4"→	Specifications Material: Constructed of complete cast All hardware provided shall b steel. Screw hardware may n Glass: Choice of clear, frosted or prin Colored glass available for et	e stainless not match paint. ismatic glass.	Finish: A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.
	9		Ballasts: Fluorescent Ballast will be ele Fluorescent sockets will be 4 quad or triple tube lamps. Electrical: 4-Pin Socket; Multi-tap 120v,	pin to accept	Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.
			240v & 277v.		Cord mounts are UL Listed for dry locations. Arm, wall, post, pendant and stem mounts are UL Listed for wet locations.
					Modifications: Consult factory for custom or modified designs.
				BLC GL	JPC NANA120v49.
CFL	-				ard Shade Voltage Finish
VTP100GL CFL Weight: 2 lbs Catalog Logic Vapor Tight Glass Light Source/ Wattage Mounting Ballast Housing Source Catalog Number 1 2 3 4 5 6				Source	Accessories Accessories
Cata	alog Number 1 2	3 4	5 6	7	8 9
	VTP100GL - CL -32WPL -	RTC – BLC	-GUPC - NA	— NA	
				_	
1	GLASS	3 BALLA	ST HOUSING	4 🛛	MOUNTING SOURCES CONT.
NA					
	(No Glass)	_	escent (WPL)		Cord Mounts
CL	(Clear Glass)	Fluor	escent (WPL)		cord with 1" x 5 3/8" canopy)
CL FR	(Clear Glass) (Frosted Glass)	Fluon RTC (WPL Ballast Canopy)			cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy)
CL FR PR	(Clear Glass) (Frosted Glass) (Prismatic Glass)	Fluor		WHC (6' white	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts
CL FR PR BLU	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass)	Fluon RTC (WPL Ballast Canopy)	py/No Spun Cover)	WHC (6' white 3/4" (1"OD Rigid	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy)
CL FR PR BLU AMB	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass)	Fluon RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano	py/No Spun Cover)	WHC (6' white 3/4" (1"OD Rigid	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48
CL FR PR BLU AMB GRN	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Green Glass)	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla	py/No Spun Cover)	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3 3ST60 3ST72	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96
CL FR PR BLU AMB	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass)	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT	py/No Spun Cover) st Housing)	WHC (6' white 3/4" (1"OD Rigit 3ST6 3ST12 3 3ST60 3ST72 5	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48
CL FR PR BLU AMB GRN RED	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Green Glass) (Red Glass)	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT	py/No Spun Cover) st Housing) ING SOURCES ast back plate included)	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 : 3ST60 3ST72 5 NA (Note)	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard)
CL FR PR BLU AMB GRN	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Green Glass)	Fluon RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24	py/No Spun Cover) st Housing) ING SOURCES ast back plate included)	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA GUP (W	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) //ire Guard)
CL FR PR BLU AMB GRN RED	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Green Glass) (Red Glass)	Fluon RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA GUP (W	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard)
CL FR PR BLU AMB GRN RED BG	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Green Glass) (Red Glass) (Ball Glass White Only)	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA GUP (W GUPC (Cal	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) //ire Guard)
CL FR PR BLU AMB GRN RED BG	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL)	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA GUP (W GUPC (Ca 6 (Ca)	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) //ire Guard) //ire Guard) //ire Guard) SHADE ACCESSORIES
CL FR PR BLU AMB GRN RED BG 2	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM318	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 GU24 26WP	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM318	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 all Mounts	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA GUP (W GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) //ire Guard) //ire Guard) //ire Guard) SHADE ACCESSORIES
CL FR PR BLU AMB GRN RED BG 2	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM318	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 all Mounts	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 GU24 26WP 32WP	(Clear Glass) (Frosted Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Green Glass) (Green Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM318 Pc PM10 PM20	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 all Mounts	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP 26WP 32WP 26WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM35 WM40 WM318 Pot PM10 PM20 Pen	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 fall Mounts	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM35 WM40 WM318 Pc PM10 PM20 Pen 2 Light Penda	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 all Mounts ost Mounts	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP 26WP 32WP 26WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM35 WM40 WM318 Pc PM10 PM20 Pen 2 Light Penda	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 fall Mounts all Mounts dant Mounts ant 100w Vapor Tights END18 21PEND24 21PEND36	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP 26WP 32WP 26WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Ballast 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 WW35 WM40 WM35 WM40 WM35 PM10 PM20 Pen 2 Light Penda 21PEND6 21PEND12 21P 21PEND48 21PEND60 21	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 fall Mounts all Mounts dant Mounts ant 100w Vapor Tights END18 21PEND24 21PEND36	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP 26WP 32WP 26WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM35 WM40 WM35 Pd PM10 PM20 Pen 2 Light Penda 21PEND6 21PEND12 21P 21PEND48 21PEND60 211 3 Light Penda	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 fall Mounts fall Mounts ast Mounts dant Mounts ant 100w Vapor Tights END18 21PEND24 21PEND36 PEND72 21PEND96	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP 26WP 32WP 26WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 W WM35 WM40 WM35 WM40 WM35 Pd PM10 PM20 Pen 2 Light Penda 21PEND6 21PEND12 21P 21PEND48 21PEND60 211 3 Light Penda	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 all Mounts all Mounts adant Mounts ant 100w Vapor Tights END18 21PEND24 21PEND36 PEND72 21PEND96 ant 100w Vapor Tights END18 31PEND24 31PEND36	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP 26WP 32WP 26WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 WWM35 WM40 WM35 WM40 WM35 PM10 PM20 Pen 2 Light Penda 21PEND6 21PEND12 21P 21PEND6 31PEND12 31P 31PEND6 31PEND60 31	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 all Mounts all Mounts adant Mounts ant 100w Vapor Tights END18 21PEND24 21PEND36 PEND72 21PEND96 ant 100w Vapor Tights END18 31PEND24 31PEND36	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)
CL FR PR BLU AMB GRN RED BG BG 2 CU24 26WP 32WP 26WP 32WP 26WP	(Clear Glass) (Frosted Glass) (Frismatic Glass) (Prismatic Glass) (Blue Glass) (Amber Glass) (Amber Glass) (Green Glass) (Red Glass) (Red Glass) (Ball Glass White Only) LIGHT SOURCE & WATTAGES Flourescent (WPL) Socket Option L LDIM LDIM CH Fluorescent dimming is 0-10y and ballast must be located within	Fluor RTC (WPL Ballast Canopy) RTCNC (WPL Ballast Cano DBH (Dimming WPL Balla 4 MOUNT Arm Mounts (C E6 E9 E13 E22 E23 E24 WW35 WM40 WM35 WM40 WM35 PM10 PM20 Pen 2 Light Penda 21PEND6 21PEND12 21P 21PEND6 31PEND60 311 3 Light Penda 31PEND6 31PEND60 311 4 Light Penda	py/No Spun Cover) st Housing) ING SOURCES ast back plate included) E25 E26 E27 E36 E39 all Mounts all Mounts ast Mounts dant Mounts ext Mounts ant 100w Vapor Tights END18 21PEND24 21PEND36 PEND72 21PEND96 ant 100w Vapor Tights END18 31PEND24 31PEND36 PEND72 31PEND96	WHC (6' white 3/4" (1"OD Rigid 3ST6 3ST12 3ST60 3ST72 5 NA NA (Ni GUPC (Ca 6 NA	cord with 1" x 5 3/8" canopy) cord with 1" x 5 3/8" canopy) Stem Mounts d Stems with STC Flat Canopy) 3ST18 3ST24 3ST36 3ST48 3ST96 GUARD o Guard) fire Guard) fire Guard) SHADE ACCESSORIES (No Accessory)

WARRANTY

See www.anplighting.com for complete fixture warranty.

© 2016 ANP Lighting. All rights reserved. These specifications are intended for general purposes only. ANP reserves the right to change material or design, without prior notice, in a continuing effort to upgrade its products.

12202017



Specifications VTP100GL-CL-32WPL-RTC-BLC-GUPC

Project: _____

Customer:

Fixture Type: _____ Quantity: _____

81

80

67

66

68

117

129 Extreme Chrome

119 Butterscotch

115 Caramel

126 Black Silver

Textured Desert Stone

64

65

82

69

Consult factory for additional paint charges and availability

116 Candy Apple Red

122 Cobalt Blue

128 Graystone

113 Gunmetal Gray

7 ACCESSORIES		8	8 VOLTAGES			9 FINISHES					
СВС	(Cast back plate Spun Alum Cover)	120	208	240	277						
с	(Button Photo Cell) Remote Only			1		Standard Grade	Marine Grade		Standard Grade	Marine Grade	
C	(Scroll for Arms)					40	NA	- Raw Unfinished	53	100	- Copper Clay
LC	(Sloped Ceiling Mount)					41	101	Black	56		Silver
Q	(Square Back Plate)					42	102	Forest Green	61	106	Black Verde
WL	(Swivel)					43	114	Bright Red	70	118	Painted Chrom
вк	(Turnbuckle Kit)					44	107	White	71	105	Painted Coppe
						45	112	Bright Blue	72	108	Textured Black
						46	123	Sunny Yellow	73	125	Matte Black
						47	120	Aqua Green	76	121	Textured Architectural Bronze
						49	NA	Galvanized	77	127	Textured White
						50	111	Navy	78	124	Textured Silver
						51	103	Architectural Bronze	10	130	Aspen Green
						52	104	Patina Verde	11	131	Cantaloupe
						12	133	Lilac	13	132	Putty
						Premium Grade	Marine Grade		Premium Grade	Marine Grade	

© 2016 ANP Lighting. All rights reserved. These specifications are intended for general purposes only. ANP reserves the right to change material or design, without prior notice, in a continuing effort to upgrade its products.



Specifications VTP100GL-CL-32WPL-RTC-BLC-GUPC

