| ANPLighting |
|--------------------------|
| INNOVATIVE SITE LIGHTING |

Specifications VTP200GL-CL-42WPL-RTC-BLC-GUP

| INNOVATIVE SITE LIGHTING | | | | | | | | |
|--|--------------------------------|---|------------------------------|---|--|--------------------------------------|---|--|
| | | Project: | | | | | | |
| | | Fixture Type | | | e: Quantity: | | | |
| | | | | Customer: | | | | |
| | | | | | | | | |
| FF 7 | | | Cine | -:f:t: | Ma | | Engineering soci | |
| | <u></u> ,≪—5"— | | Spec Material: | cifications | | alconoing and pr | etreatment process for | |
| | | | Constructed | d of complete cast e provided shall be | | maximum paint a | adhesion. | |
| | | $\overline{\mathcal{A}}$ | | w hardware may n | | Marine grade fini humidity and UV | sh provides superior sa protection. This coating 3000 hours of continuo | |
| | | | Glass: Choice of c | lear, frosted or pris | matic glass. | salt spray, come | s with a 5-vear warrantv | |
| | | | Colored gla | ss available for ex | tra charge. | and is available i surface. | n either a textured or gl | |
| | 10 3/4" | | Ballasts: Fluorescent | t Ballast will be ele | ctronic. Fluo- | Certifications: | | |
| | | | rescent soc or triple tub | kets will be 4 pin t e lamps. | o accept quad | Arm, wall, post, r | UL Listed for dry location pendant and stem mount | |
| Carlos and the service | | | Electrical: | | | are UL Listed for | wet locations. | |
| a> | |) | 4-Pin Socke 277v. | et; Multi-tap 120v, | 208v, 240v & | | or custom or modified | |
| 0 | | | Finish | | | designs. | | |
| | | | Finish: A polyester | powder coat high ically applied and | quality finish is | | | |
| | | | for exception | nal durability and ndergo an intensive | color retention. | | | |
| VTP200GL | Weight: 3 lbs | Catalog Logic | FIGUUCIS UI | idergo an intensiv | s inve-siep | | | |
| | Traight. 0 103 | | - CL -42WPL | RTC | | NA | NA120v | |
| CFL | | Vapor Tight | | Ballast Housing Me | | Shade | Accessories Voltage F | |
| | | Style | Glass Wattage | S | ource | Accessories | Accessories voltage i | |
| | | | | | | | | |
| Catalog Number 1 | 2 3 | 4 | 5 | 6 | 7 | 8 | 9 | |
| VTP200GL - CL - | -42WPL - RTC | - BLC - | - GUP - | NA | – NA | | | |
| VIP200GL CL | 42WPL RIC | BLC | GUP | NA | NA NA | | | |
| 1 GLASS | 2 | BVITVE | T HOUSING | | 4 MC | | CES CONT | |
| NA (No Glass) | 3 | DALLAS | THOUGHNU | | - | Cord Moun | | |
| CL (Clear Glass) | | Fluorescent (WPL) | | | BLC (6' black co | ord with 1" x 5 3/8" of | | |
| FR (Frosted Glass) | RTC (WP | RTC (WPL Ballast Canopy) | | | WHC (6' white cord with 1" x 5 3/8" canopy) | | | |
| PR (Prismatic Glass) | RTCNC | RTCNC (WPL Ballast Canopy/No Spun Cover) | | | Stem Mounts | | | |
| BLU (Blue Glass) | | | | | 3/4" (1"OD Rigid Stems with STC Flat Canopy) | | | |
| AMB (Amber Glass) | DBH (Dir | DBH (Dimming WPL Ballast Housing) | | | | 3ST6 3ST12 3ST18 3ST24 3ST36 3ST48 | | |
| GRN (Green Glass) | | | | | 3ST60 3ST72 3 | ST96 | | |
| RED (Red Glass) | 4 | MOUNTIN | G SOURCES | | 5 | GUARD | | |
| | | Arm Mounts (Cast | t back plate included | (t | | | , | |
| 2 LIGHT SOURCE & WATTA | AGES | 13 E22 E23 E24 E | 25 E26 E27 E36 | E39 | ````` | Guard) | | |
| _ | | Wall | Mounts | | | Guard) | | |
| Flourescent (WPL) | WM35 | | | | 0010 (000 | Guardy | | |
| GU24 Socket Option 26WPL | WM40 | | | | 6 | SHADE ACCES | SORIES | |
| 32WPL | WM318 | Boot | Mounts | | NA (N | lo Accessory) | | |
| 42WPL | PM10 | FUSI | iniounts | | VTS (9 | 3/4" Angle Ring) | | |
| 26WPLDIM | PM20 | | | | | | | |
| 32WPLDIM | | Penda | nt Mounts | | | | | |
| 42WPLDIM | | | 200w Vapor Tights | | | | | |
| (Compact Fluorescent dimming is 0-10v and ballast r 12" of lamp) | nust be located within 22PEND6 | 22PEND6 22PEND12 22PEND18 22PEND24 22PEND36 | | | | | | |
| | 22PEND4 | 8 22PEND60 22PE | ND72 22PEND96 | | | | | |
| | | 3 Light Pendant | t 200w Vapor Tights | | | | | |
| | 32PEND6 | 32PEND6 32PEND12 32PEND18 32PEND24 32PEND36 | | | | | | |
| | 32PEND4 | 8 32PEND60 32PE | | | | | | |
| | | - | 200w Vapor Tights | | | | | |
| WARRANTY | | 42PEND12 42PE | | 42PEND36 | | | | |
| | | 8 42PEND60 42PE | ND72 42PEND96 | | | | | |
| See www.anplighting.com for complete fi | xture warranty. | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | 000 540 000- | |

© 2016 ANP Lighting. All rights reserved. These specifications are intended for general purposes only. ANP reserves the right to change material or design, without prior notice, in a continuing effort to upgrade its products.



Specifications VTP200GL-CL-42WPL-RTC-BLC-GUP

Project:

Fixture Type: ____

Customer:

9

67

66

68

119

_____ Quantity: _ **FINISHES** Standard Grade Standard Grade Marine Grade Marine Grade Raw Unfinished 40 NA 53 100 Copper Clay 41 101 Black 56 109 Silver 42 102 Forest Green 61 106 Black Verde 43 118 Painted Chrome 114 Bright Red 70 44 105 Painted Copper 107 White 71 45 Bright Blue 72 108 Textured Black 112 Sunny Yellow 125 Matte Black 46 123 73 Textured Architectural Bronze 47 Aqua Green 76 121 120 127 Textured White 49 NA Galvanized 77 50 111 Navy 78 124 Textured Silver Architectural Bronze 51 10 130 Aspen Green 103 131 Cantaloupe 52 104 Patina Verde 11 12 133 Lilac 13 132 Putty Premium Marine Premium Marine Grade Grade Grade Grade 129 Extreme Chrome 81 64 116 Candy Apple Red Textured Desert Stone 80 117 65 122 Cobalt Blue

Consult factory for additional paint charges and availability

82

69

128 Graystone

113 Gunmetal Gray

Butterscotch

115 Caramel

126 Black Silver

| 7 | ACCESSORIES | |
|-----|-----------------------------------|--|
| СВС | (Cast back plate Spun Alum Cover) | |
| PC | (Button Photo Cell) Remote Only | |
| sc | (Scroll for Arms) | |
| SLC | (Sloped Ceiling Mount) | |
| SQ | (Square Back Plate) | |
| SWL | (Swivel) | |
| твк | (Turnbuckle Kit) | |
| | | |

| | | | Custo | | | | | |
|-----|----------|-----|-------|--|--|--|--|--|
| 8 | VOLTAGES | | | | | | | |
| 120 | 208 | 277 | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |



Specifications VTP200GL-CL-42WPL-RTC-BLC-GUP



2202017