

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____



illuminating
ENGINEERING SOCIETY

Specifications

Material:
RLM shades are constructed of heavy duty spun aluminum. Wall back plate and ballast housing are cast aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Glass:
Choice of clear, frosted or prismatic glass.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.


Electrical:
Medium Base Socket, 200w Maximum.

Certifications:
Cord mounts are UL Listed for dry locations. Arm mount, stem mount and wall mount are UL Listed for wet locations.

Modifications:
Consult factory for custom or modified luminaires.



Quick Ship



Weight: 1.5 lbs

Catalog Logic

Q-M714 - E6 - 51
RLM Style Mounting Source Finish

M714

200w max Incandescent

Catalog Number

Q-M714 - E6 - 51

1 MOUNTING SOURCES

Arm Mounts (Cast back plate included)

E3 E4 **E6** E7 E8
E10 E11 E12 E18 E25

ARM MOUNTS | Dimensions are Projection x Height | CB included with all arms



E6 | 26" x 9 1/4"

2 FINISHES

Standard Grade	Marine Grade	Standard Grade	Marine Grade
40	NA	53	100
41	101	56	109
42	102	61	106
43	114	70	118
44	107	71	105
45	112	72	108
46	123	73	125
47	120	76	121
49	NA	77	127
50	111	78	124
51	103	10	130
52	104	11	131
12	133	13	132

Premium Grade	Marine Grade	Premium Grade	Marine Grade
81	129	64	116
80	117	65	122
67	119	82	128
66	115	69	113
68	126	83	134

Consult factory for additional paint charges and availability