

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

Specifications

Material:
RLM shades are constructed of heavy duty spun aluminum. Wall back plate and driver housing are cast aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint.

Glass:
Choice of clear, frosted or prismatic glass up to **16w Max.**

Electrical:
GU24 socket, 120V only.
Universal voltage 120-277 is standard.
0-10V, TRIAC and ELV dimming protocols are standard for LED modules. (12w is TRIAC dimming & 120v only; 24w is 0-10v only)

See page 2 table for LED module and driver specs, voltage and dimming protocols.



Certifications:
Cord mounts are UL Listed for dry locations. Arm mount, stem mount and wall mount are UL Listed for wet locations.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified luminaires.

ORB218

Weight: 3 lbs

LED

Catalog Logic



Catalog Number	1	2	3	4	5	6	7	8	9	10
	ORB218	FR	M024LD	D	W	40K	RTC	UNV	BLC	

1	GLASS
Up to 16w Max	
CL	(Clear Glass)
FR	(Frosted Glass)
PR	(Prismatic Glass)

2	LIGHT SOURCE & WATTAGES
GU24	(GU24 Socket Only, 120V only)
M012LD	(12w, 750 lumen, Cree module) Integral driver, 120V, TRIAC dimming & narrow distribution only.
M009LD	(9w, 850 lumen, Cree module)
M010LD	(10w, 1250 lumen, Cree module)
M016LD	(16w, 2000 lumen, Cree module)
M024LD	(24w, 3000 lumen, Cree module)

3	DIMMING
D	(Dimming)
See page 2 table for LED engine and driver specs, voltage and dimming protocols.	

4	DISTRIBUTION
W	(T5 Wide Distribution with Dome LED Lens)
N*	(T5 Narrow Distribution with Flat LED Lens)
*12w is narrow only, select "N".	

5	COLOR TEMPERATURE (CCT)
27K	(2700K)
30K	(3000K) (Not Sunset Dim)
35K	(3500K) (Not Sunset Dim)
40K	(4000K) (Not Sunset Dim)

6	DRIVER HOUSING
RTC	(Driver Canopy)
RTCNC	(Driver Canopy/No Spun Cover)
NA	(Housing not required for 12w)

7	VOLTAGE
UNV	(120-277)

8	MOUNTING SOURCES
Arm Mounts (Cast back plate included (CB))	
E3 E4 E6 E8 E9 E13 E15 E18	
E20 E22 E25 E26	
(See Step 5 for Driver Housing Options)	
Wall Mounts	
WM40	
WM54	
WM74	
WM317	
WM84	
Post Mounts (Postline driver only; 4" OD/.125 pole required)	
PM10	
PM20	
PM30	
PM40	
PM50	
PM319	

9	ACCESSORIES
CBC	(Cast back plate Spun Alum Cover)
GR18	(18" Wire Grill)
PC	(Button Photo Cell) Remote Only
SC	(Scroll for Arms)
SLC	(Sloped Ceiling Mount, 20° Max)
SQ	(Square Back Plate)
SWL	(Swivel)
TBK	(Turn Buckle Kit)

10	CORD MOUNTS
BLC	(6' black cord with 1" x 5 3/8" canopy)
WHC	(6' white cord with 1" x 5 3/8" canopy)

10	STEM MOUNTS
1/2" (13/16" OD Rigid Stems with STC Flat Canopy)	
2ST6	2ST12 2ST18 2ST24 2ST36 2ST48
2ST60	2ST72 2ST96
3/4" (1" OD Rigid Stems with STC Flat Canopy)	
3ST6	3ST12 3ST18 3ST24 3ST36 3ST48
3ST60	3ST72 3ST96
(See Step 5 for Driver Housing Options)	

10	FINISHES																																																								
	<table border="1"> <thead> <tr> <th>Standard Grade</th> <th>Marine Grade</th> <th>Standard Grade</th> <th>Marine Grade</th> </tr> </thead> <tbody> <tr> <td>40</td> <td>NA</td> <td>53</td> <td>100</td> </tr> <tr> <td>41</td> <td>101</td> <td>56</td> <td>109</td> </tr> <tr> <td>42</td> <td>102</td> <td>61</td> <td>106</td> </tr> <tr> <td>43</td> <td>114</td> <td>70</td> <td>118</td> </tr> <tr> <td>44</td> <td>107</td> <td>71</td> <td>105</td> </tr> <tr> <td>45</td> <td>112</td> <td>72</td> <td>108</td> </tr> <tr> <td>46</td> <td>123</td> <td>73</td> <td>125</td> </tr> <tr> <td>47</td> <td>120</td> <td>76</td> <td>121</td> </tr> <tr> <td>49</td> <td>NA</td> <td>77</td> <td>127</td> </tr> <tr> <td>50</td> <td>111</td> <td>78</td> <td>124</td> </tr> <tr> <td>51</td> <td>103</td> <td>10</td> <td>130</td> </tr> <tr> <td>52</td> <td>104</td> <td>11</td> <td>131</td> </tr> <tr> <td>12</td> <td>133</td> <td>13</td> <td>132</td> </tr> </tbody> </table>	Standard Grade	Marine Grade	Standard Grade	Marine Grade	40	NA	53	100	41	101	56	109	42	102	61	106	43	114	70	118	44	107	71	105	45	112	72	108	46	123	73	125	47	120	76	121	49	NA	77	127	50	111	78	124	51	103	10	130	52	104	11	131	12	133	13	132
Standard Grade	Marine Grade	Standard Grade	Marine Grade																																																						
40	NA	53	100																																																						
41	101	56	109																																																						
42	102	61	106																																																						
43	114	70	118																																																						
44	107	71	105																																																						
45	112	72	108																																																						
46	123	73	125																																																						
47	120	76	121																																																						
49	NA	77	127																																																						
50	111	78	124																																																						
51	103	10	130																																																						
52	104	11	131																																																						
12	133	13	132																																																						

Premium Grade	Marine Grade	Premium Grade	Marine Grade
81	129	64	116
80	117	65	122
67	119	82	128
66	115	69	113
68	126	83	134

Consult factory for additional paint charges and availability

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

LED PERFORMANCE				
MODULE				
LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy
9W	2700K	850	11W	97
	3000K	850	11W	97
	3500K	850	11W	97
	4000K	850	11W	97
10W	2700K	1250	12W	125
	3000K	1250	12W	125
	3500K	1250	12W	125
	4000K	1250	12W	125
12W	2700K	750	12W	65
	3000K	750	12W	65
	3500K	750	12W	65
	4000K	750	12W	65
16W	2700K	2000	19W	125
	3000K	2000	19W	125
	3500K	2000	19W	125
	4000K	2000	19W	125
24W	2700K	3000	28W	125
	3000K	3000	28W	125
	3500K	3000	28W	125
	4000K	3000	28W	125

MODULE SPECIFICATION
<ul style="list-style-type: none"> • Efficacy 65-125 lumens per watt • Dimmable down to 1% • Life: L70 50,000 hours • Color temp: 2700K,3000K,3500K and 4000K • CRI: >90

MODULE DRIVER SPECIFICATION
<ul style="list-style-type: none"> • Input Voltage: 120-277 Volts; 50/60Hz • 0-10V, TRIAC and ELV dimming protocols are standard. (24w is 0-10v only) • Output Current: Constant Current: 440mA to 940mA (model dependent) • Driver Efficiency > 80%; Power Factor > 0.9 • Integral Surge Protection in conformance to ANSI C62.41 Category A

MODULE LISTINGS
<ul style="list-style-type: none"> • Fully compliant with the RoHS Directive • Certifications: CE/UL

WARRANTY
<p>See www.anplighting.com for complete fixture warranty.</p> <p>LED warranty information</p> <ul style="list-style-type: none"> • 5 year limited warranty* <p>*Limited Warranty: A typical year is defined as 4380 hours of operation.</p>

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

ARM MOUNTS | Dimensions are Projection x Height | CB included with all arms

 E3 32" x 11 7/8"	 E4 26" x 14"	 E6 26" x 9 1/4"	 E8 29 1/4" x 12 1/2"
 E9 28" x 40 5/8"	 E13 34" x 34 3/8"	 E15 13 3/8" x 10 1/2"	 E18 27 3/4" x 21 3/8"
 E20 7" x 4 1/2"	 E22 7 1/2" x 4 1/2"	 E25 23" x 5 1/4"	 E26 8 1/8" x 6"









GLASS UP TO 16W MAX	
Glass Legend: CL = Clear FR = Frosted PR = Prismatic	
Glass Only	
	GLCL
	GLFR
	GLPR

Driver Housing	
	RTC
	RTCNC

WALL MOUNTS | Dimensions are Projection x Height | **POST MOUNTS** | Dimensions are Projection x Height

 WM40 13 7/8" x 14 3/4"	 WM54 23 3/8" x 18"	 PM10 14 1/2" x 25"	 PM20 30 1/8" x 25"
 WM74 22" x 26 1/2"	 WM317 15" x 12 3/4"	 PM30 21 5/8" x 28 7/8"	 PM40 43 3/8" x 28 7/8"
 WM84 26 1/2" x 57 1/4"		 PM50 27" x 38"	 PM319 16 5/8" x 27 1/2"

ACCESSORIES

 CBC	 GR18	 PC	 SC
 SLC	 SQ	 SWL	 TBK