Specifications DD20

Project:	
Fixture Type:	Quantity:
Customer:	·

12 1/4" 9 1/4"	
20"	~ 1

Specifications

Material: RLM shades are constructed of heavy duty spun aluminum. Wall back plate and ballast housing are cast aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match

Glass: Choice of clear, frosted or prismatic glass.

Electrical: Medium Base Socket, 200w Maximum or GU24 Socket.

Approximately 12" of pull wire extends from fixure. Additional pull wire provided for post mount arms and wall mounts.

Certifications:

Cord mounts are UL Listed for dry locations. Arm mount, stem mount and wall mount are UL Listed for wet locations. Catalog Logic DD20 -

Finish:

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Tilluminating

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss

Modifications: Consult factory for custom or modified designs.

E6 _ 100GLCL _ CBC - 72

DD20 200w Max

Catalog Number

Weight: 6.0 lbs EPA: 0.92

1

Medium Base

RLM Light Glass & Mounting Style Accessories Finish Source Source Guards 2 3 4 5

MB₁-

Cala	alog Number
	DD20 -
1	LIGHT SOURCE & WATTAGES
GU24	4 (GU24 Socket)
МВ	(Medium Base Socket, 200w Max)
2	MOUNTING SOURCES*
	Arm Mounts (Cast back plate included)
E3 E4	4 E6 E8 E9 E10 E11 E12 E15 E18 E24 E25
	Wall Mounts
WM3	5 WM41 WM55 WM318
	Post Mounts
PM10	PM20 PM30 PM40 PM50 PM319
	Cord Mounts** (Includes 1" x 5 3/8" canopy) (See page 3 for color cord style)
	SJT Cord
BLC	(6' Black SJT Cord) WHC (6' White SJT Cord)

WICONTI	NG SOURCES		
Arm Mounts (Ca	ast back plate included)		
E3 E4 E6 E8 E9 E10 E11 E1	2 E15 E18 E24 E25		
W	all Mounts		
WM35 WM41 WM55 WM3	18		
Po	est Mounts		
PM10 PM20 PM30 PM40 P	M50 PM319		
Cor (Includes 7 (See page 3	d Mounts** " x 5 3/8" canopy) for color cord style)		
S	JT Cord		
BLC (6' Black SJT Cord)	WHC (6' White SJT Cord)		
Solid Fabr	ic Colored Cords		
BLSF (6' Black)	ORSF (6' Orange)		
GYSF (6' Gray)	LGSF (6' Lime Green)		
CHSF (6' Chocolate Brown)	KGSF (6' Kelly Green)		
WHSF (6' White)	CBSF (6' Cobalt Blue)		
CASF (6' Cardinal)	SBSF (6' Sky Blue)		
Patterned Fa	bric Colored Cords		
BWHPF (6' Black/White Houndstooth)	BIHPF (6' Brown/Ivory Houndstooth)		
GYCPF (6' Gray/Citrus Yellow)	MOSPF (6' Magenta/Orange Stripe)		
NMTPF (6' Navy Mini Tweed)			
Glossy Fab	ric Colored Cords		
GMGF (6' Gun Metal)	SSGF (6' Sterling Silver)		
CPGF (6' Copper Penny)	BRGF (6' Bronze)		
GOGF (6' Gold)			
Cab (Includes 1	le Mounts** l" x 5 3/8" canopy)		
SSC-BLC (Stainless steel ca	able with 6' Black SJT Cord)		
SSC-WHC (Stainless steel ca	able with 6' White SJT Cord)		
SCC-XXXX (Stainless steel ca Replace XXXX w	able with 6' Color cord. vith color cord designation above)		
**Cord/Cable Canopy finish	will match fixture finish.		
	em Mounts STC Flat Canopy)		
1/2" (13/16" OD) Rigid	3/4" (1" OD) Rigid Stems		
2ST6 2ST12 2ST18	3ST6 3ST12 3ST18		
2ST24 2ST36 2ST48	3ST24 3ST36 3ST48		
2ST60 2ST72 2ST96	3ST60 3ST72 3ST96		

*Arm mount, Wall mount or Stem finish will match fixture finish.

3	GLASS & GUARD		
Up to 100w Options			
100GLCL	(Clear Glass)		
100GLFR	(Frosted Glass)		
100GLPR	(Prismatic Glass)		
100GLCLGUP	(Clear Glass & Small Wire Guard)		
100GLFRGUP (Frosted Glass & Small Wire Guard)			
100GLPRGUP	(Prismatic Glass & Small Wire Guard)		
100GLCLGUP	C(Clear Glass & Cast Guard)		
100GLFRGUP	C (Frosted Glass & Cast Guard)		
100GLPRGUP	C (Prismatic Glass & Cast Guard)		
100GLGUP	(Small Wire Guard with No Glass)		
100GLGUPC	(Cast Guard with No Glass)		
	Up to 200w Options		
200GLCL	(Clear Glass)		
200GLFR	(Frosted Glass)		
200GLPR	(Prismatic Glass)		
200GLCLGUP	(Clear Glass & Large Wire Guard)		
200GLFRGUP	(Frosted Glass & Large Wire Guard)		
200GLPRGUP	(Prismatic Glass & Large Wire Guard)		
200GLCLGUP	C (Clear Glass & Large Cast Guard)		
200GLFRGUP	C (Frosted Glass & Large Cast Guard)		
200GLPRGUP	C (Prismatic Glass & Large Cast Guard)		
200GLGUP	(Large Wire Guard with No Glass)		
200GLGUPC (Large Cast Guard with No Glass)			

GLASS & GUARD

WARRANTY

See www.ANPlighting.com for complete fixture warranty

4	ACCESSORIES*
СВС	(Cast back plate Spun Alum Cover)*
PC	(Button Photo Cell) Remote Only
sc	(Scroll for Arms)*
SLC	(Sloped Ceiling Mount Canopy, 20° Max)*
sq	(Square Back Plate)*
SWL	(Adjustable Locking Swivel)*
твк	(Turn Buckle Kit)*
*Acce	ssory finish will match fixture finish.

5 _{*M}	arine Grade		SHES nas an additional charge		
Standard Colors	Standard Grade	Marine	Premium Colors	Premium Grade	Marin
Aspen Green	10	10M	High Gloss Black	01	011
Cantaloupe	11	11M	Arctic Silver	14	14N
Lilac	12	12M	Candy Apple Red	64	64N
Putty	13	13M	Cobalt Blue	65	65N
Raw Unfinished	40	NA	Caramel	66	66N
Black	41	41M	Butterscotch	67	67N
Forest Green	42	42M	Black Silver	68	68N
Bright Red	43	43M	Gunmetal Gray	69	69N
White	44	44M	Mayan Gold	79	NA
Bright Blue	45	45M	Textured Desert Stone	80	801
Sunny Yellow	46	46M	Extreme Chrome	81	81N
Aqua Green	47	47M	Graystone	82	82N
Galvanized	49	NA	Oil Rubbed Bronze	83	83N
Navy	50	50M	Carbon Graphite	96	96N
Architectural Bronze	51	51M			
Patina Verde	52	52M			
Copper Clay	53	53M			
Silver	56	56M			
Black Verde	61	61M			
Painted Chrome	70	70M			
Painted Copper	71	71M			
Textured Black	72	72M			
Matte Black	73	73M			
Textured Architectural	76	76M			
Textured White	77	77M			
Textured Silver	78	78M			

Project: _ _____ Quantity: ___ Fixture Type: ___ Customer: **GLASS & GUARDS** ARM MOUNTS | Dimensions are Projection x Height | CB included with all arms **UP TO 200W MAX** Glass Legend: CL = Clear FR = Frosted PR = Prismatic 100 = Small 200 = Large Glass Only (9 1/4" H X 5" W) 200GLCL **E6** | 26" x 9 1/4" E3 | 32" x 11 7/8" E4 | 26" x 14" E8 | 29 1/4" x 12 1/2" 200GLFR 200GLPR Glass with Cast Guard (10 1/4" H X 5 1/2" W) 200GLCLGUPC **E10** | 52 1/4" x 18" E9 | 28" x 40 5/8" E11 | 35 1/4" x 17 1/4" E12 | 37 3/8" x 2" 200GLFRGUPC 200GLPRGUPC Glass with Wire Guard (10 1/4" H X 5" W) 200GLCLGUP **E15** | 13 3/8" x 10 1/2" E18 | 27 3/4" x 21 3/8" **E24** | 10" x 2" **E25** | 23" x 5 1/4" 200GLFRGUP 200GLPRGUP GUPC Guard Only (10 1/4" H X 5 1/2" W) WALL MOUNTS | Dimensions are Projection x Height | POST MOUNTS | Dimensions are Projection x Height 200GLGUPC (Cast Guard) GUP Guard Only (10 1/4" H X 5" W) WM35 | 20 1/2" x 25" WM41 | 10 1/2" x 14 3/4" PM20 | 30 1/8" x 25" PM10 | 14 1/2" x 25" 200GLGUP (Wire Guard) WM55 | 20 5/8" x 14 1/4" WM318 | 12" x 12 3/4" PM40 | 43 3/8" x 28 7/8" PM30 | 21 5/8" x 28 7/8" PM50 | 27" x 38" PM319 | 16 5/8" x 27 1/2" **ACCESSORIES** PC SLC CBC SC

TBK

SWL

SQ

Project: _____ Quantity: _____ Customer:





