## **Specifications OSDDF30**

| <b>†</b> |
|----------|

Weight: 10.5 lbs

**Specifications** 

Material:
Dome top is constructed of heavy duty spun aluminum.
Shade is of a hard back fabric.
Driver housing is constructed of heavy duty spun aluminum.
All fasteners are stainless steel. Screw hardware may not match paint.

Electrical:
Medium Base Socket, 200w Maximum or GU24 Socket.
Approximately 12" of pull wire extends from fixure. Additional pull wire provided for post mount arms and wall mounts.

Certifications: UL Listed for dry locations.

Catalog Logic

Project: \_ Fixture Type: \_

Customer: \_

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and

Quantity: \_

Illuminating

pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Lamp Base

**FINISHES** 

OSDDF30 GY - MB - BLC - 72

Fabric

**Modifications:**Consult factory for custom or modified designs.

OSDDF30 200w Max **Medium Base** 

RLM Style

| Catalog Number |         | 1 | 2   | 3 | 4 |
|----------------|---------|---|-----|---|---|
|                | OSDDF30 | - | - – |   | _ |

| 1   | FABRIC SHADE                |
|-----|-----------------------------|
| BG  | (Beige Hard Back Fabric)    |
| вк  | (Black Hard Back Fabric)    |
| GY  | (Gray Hard Back Fabric)     |
|     |                             |
| cus | T (Custom Hard Back Fabric) |

| 2    | LAMP BASE               |
|------|-------------------------|
| МВ   | (Medium Base, 200w Max) |
| GU24 | (GU24 Base)             |

MOUNTING COURCES\*

| 3 MOUNTING S  | OURCES"  |
|---|--|
| Cable Mo<br>(Includes 1" x 5 3                                |  |
| SSC-BLC (Stainless steel cabl                                 | e with 6' Black SJT Cord)                        |
| SSC-WHC (Stainless steel cabl                                 | le with 6' White SJT Cord)                       |
| SSC-XXXX (Stainless steel cabl<br>Replace XXXX with<br>below) | le with 6' Color cord.  n color cord designation |
| **Cord/Cable Canopy finish w                                  | ill match fixture finish.                        |
| SJT Co  | ord  |
| BLC (6' Black SJT Cord) W                                     | 'HC (6' White SJT Cord)                          |
| Solid Fabric Co   | lored Cords                                      |
| BLSF (6' Black) O   | RSF (6' Orange)                                  |

LGSF (6' Lime Green)

CBSF (6' Cobalt Blue)

SBSF (6' Sky Blue)

BRGF (6' Bronze)

| Patterned Fabri                       | c Colored Cords                       |
|---------------------------------------|---------------------------------------|
| BWHPF (6' Black/White<br>Houndstooth) | BIHPF (6' Brown/Ivory<br>Houndstooth) |
| GYCPF (6' Gray/Citrus<br>Yellow)      | MOSPF (6' Magenta/Orange<br>Stripe)   |
| NMTPF (6' Navy Mini<br>Tweed)         |                                       |
| Glossy Fabric                         | Colored Cords                         |
| GMGF (6' Gun Metal)                   | SSGF (6' Sterling Silver)             |

CHSF (6' Chocolate Brown) KGSF (6' Kelly Green)

| 3    | MOUNTING SOURCES (Continued)*               |
|------|---|
|      | Stem Mounts*                                |
| 1/4" | (1/2" OD Stems with 45° Swivel Flat Canopy) |

1STS6 1STS12 1STS18 1STS24 1STS36 1STS48 1STS60 1STS72 1STS96 1/4" (1/2" OD Rigid Stems with Flat Canopy) 1STR6 1STR12 1STR18 1STR24 1STR36 1STR48 1STR60 1STR72 1STR96 \* Stem finish will match fixture finish.

| Premium Colors  High Gloss Black Arctic Silver Candy Apple Red Cobalt Blue Caramel Butterscotch Black Silver Gunmetal Gray Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze Carbon Graphite | Premium Grade  01  14  64  65  66  67  68  69  79  80  81 |
|--|---|
| Carctic Silver Candy Apple Red Cobalt Blue Caramel Butterscotch Black Silver Sunmetal Gray Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze   | 14<br>64<br>65<br>66<br>67<br>68<br>69<br>79<br>80        |
| Candy Apple Red Cobalt Blue Caramel Butterscotch Black Silver Gunmetal Gray Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze  | 64<br>65<br>66<br>67<br>68<br>69<br>79<br>80              |
| Cobalt Blue Caramel Butterscotch Black Silver Gunmetal Gray Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze  | 65<br>66<br>67<br>68<br>69<br>79<br>80<br>81              |
| Butterscotch Black Silver Sunmetal Gray Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze  | 66<br>67<br>68<br>69<br>79<br>80<br>81                    |
| Butterscotch Black Silver Gunmetal Gray Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze  | 67<br>68<br>69<br>79<br>80<br>81                          |
| Black Silver Gunmetal Gray  Mayan Gold Fextured Desert Stone Extreme Chrome Graystone  Dil Rubbed Bronze   | 68<br>69<br>79<br>80<br>81                                |
| Gunmetal Gray Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze  | 69<br>79<br>80<br>81                                      |
| Mayan Gold Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze  | 79<br>80<br>81  |
| Fextured Desert Stone Extreme Chrome Graystone Dil Rubbed Bronze   | 80  |
| Extreme Chrome Graystone Dil Rubbed Bronze   | 81  |
| Graystone<br>Dil Rubbed Bronze   |   |
| Dil Rubbed Bronze  | 82  |
|  |   |
| `arhon Granhite  | 83  |
| Darbon Grapnite  | 96  |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |
|  |   |

WARRANTY

CPGF (6' Copper Penny)

GYSF (6' Gray)

WHSF (6' White)

CASF (6' Cardinal)

See www.ANPlighting.com for complete fixture warranty

Project: \_\_\_\_\_ Quantity: \_\_\_\_\_ Customer: \_\_\_\_\_

All fabric Color Cords are three conductor, 1/4" diameter





