Specifications VEC16

		r		Proje	ect:						
		8 3/8"	Fixture Type:			Quantity:					
		Customer:			er:						
		4 1/2"	\longrightarrow	Specification					🕅 Illun	ninating	
		Material: RLM shades are co spun aluminum. Wa housing are cast alu stainless steel. Insix white finish for all c			Instructed of heavy duty A p all back plate and ballast ele uminum. All fasteners are for de of shade is reflective Pro olors except galvanized clei		Finish: A polyester powder coat high quality finish is electro-statically applied and baked at 430° or exceptional durability and color retention Products undergo an intensive five-step leansing and pretreatment process for naximum paint adhesion.				
				paint. Glass: Choice of clear, frosted or prismatic glass. Electrical: Medium Base Socket, 200w Maximum or GU24 Socket. Approximately 12" of pull wire extends from fixure. Additional pull wire provided for post		Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface. Modifications: Consult factory for custom or modified				iting iuous nty r gloss	
VEC16	Weight: 2.5 lbs	12 15/16"		mount arms and wall mo Certifications: Cord mounts are UL List Arm mount, stem mount UL Listed for wet locatio	ted for dry locations.	design	s.				
200w Max		200GL	+ 4 1/2"	Catalog Logic	C16 - MB - E	6 - 1	00GL		. 7	2	
Medium Base		.	— 16"—— •	RLM	Light mou	inting urce	Glass & Guards	Accessor	ies Fir	hish	
Catalog Number	•			Otyle			Guarus				
	VEC16	1	_ 2	-	3 _	4	_	-			
1 LIGHT SOUR	CE & WATTAGES	3	GLASS & GU	ARD*	4	AC	CESSO	RIES*			
GU24 (GU24 Socke	i)			· (· · · · · · · · · · · · · · · · · ·							
MB (Medium Bas	e Socket, 200w Max)	100GLCL	100GLCL (Clear Glass)			PC (Button Photo Cell) Remote Only					
2 MOUNTIN	IG SOURCES*	100GLFR (Frosted Glass)				SC (Scroll for Arms)* SLC (Sloped Ceiling Mount Canopy, 20° Max)*					
	st back plate included)	100GLPR (Prismatic Glass)				SQ (Square Back Plate)*					
E3 E4 E6 E8 E9 E10 E11		100GLCLGU	P (Clear Glass & Sm	all Wire Guard)	SWL (Adjus			el)*			
Wall Mounts WM35 WM41 WM55 WM318		100GLFRGU		TBK (Turn Buckle Kit)*							
	st Mounts	100GI PRGL	P (Prismatic Glass &	Small Wire Guard)	*Accessory fi			cture finish.			
PM10 PM20 PM30 PM40	PM50 PM319			,							
Corc (Includes 1	l Mounts** ' x 5 3/8" canopy) for color cord style)		PC (Clear Glass & Ca	,	5	Marine Grade	FINISH Finish has ar	S additional charge			
	for color cord stýle) JT Cord		PC (Frosted Glass & C		Standard Colors	Standard Grade	Marine	Premium Colors	Premium Grade	Marine Grade*	
	WHC (6' White SJT Cord)	100GLPRGL	IPC (Prismatic Glass 8	Cast Guard)	Aspen Green	10	10M Hig	Gloss Black	01	01M	
	c Colored Cords	100GLGUP	(Small Wire Guard	with No Glass)	Cantaloupe	11		ic Silver	14	14M	
BLSF (6' Black)	ORSF (6' Orange)	100GLGUPC	(Cast Guard with N	lo Glass)	Lilac	12		dy Apple Red	64 65	64M 65M	
GYSF (6' Gray) CHSF (6' Chocolate Browr	LGSF (6' Lime Green) h) KGSF (6' Kelly Green)		Up to 200w Opt	ions	Raw Unfinished	40		amel	66	66M	
WHSF (6' White)	CBSF (6' Cobalt Blue)	200GLCL	(Clear Glass)		Black	41	41M But	erscotch	67	67M	
CASF (6' Cardinal)	SBSF (6' Sky Blue)	ZUUGLCL	(Clear Glass)		Forest Green	42		k Silver	68	68M	
	pric Colored Cords	200GLFR	(Frosted Glass)		Bright Red White	43 44		imetal Gray	69 79	69M	
BWHPF (6' Black/White Houndstooth)	BIHPF (6' Brown/Ivory Houndstooth)	200GLPR	(Prismatic Glass)		Bright Blue	44		ured Desert Stone	79 80	NA 80M	
GYCPF (6' Gray/Citrus	MOSPF (6' Magenta/Orange	200GLCLGU	P (Clear Glass & Lar	ge Wire Guard)	Sunny Yellow	46		eme Chrome	81	81M	
Yellow) NMTPF (6' Navy Mini	Stripe)		P (Frosted Glass & La		Aqua Green	47		ystone	82	82M	
Tweed)				• ·	Galvanized	49 50		Rubbed Bronze	83 96	83M 96M	
	ic Colored Cords	200GLPRGL	IP (Prismatic Glass &	Large Wire Guard)	Navy Architectural Bronze	50	50M Car 51M	ооп отарпіце	30	Moe	
GMGF (6' Gun Metal) CPGF (6' Copper Penny)	SSGF (6' Sterling Silver) BRGF (6' Bronze)	200GLCLGU	PC (Clear Glass & Lar	ge Cast Guard)	Patina Verde	52	52M				
GOGF (6' Gold)		200GLFRGU	PC (Frosted Glass & L	arge Cast Guard)	Copper Clay	53	53M				
. ,	e Mounts** ' x 5 3/8" canopy)		IPC (Prismatic Glass 8		Silver	56	56M				
	cable with 6' Black SJT Cord)				Black Verde Painted Chrome	61 70	61M 70M				
	I cable with 6' White SJT Cord)	200GLGUP	(Large Wire Guard	l with No Glass)	Painted Copper	71	71M				
SCC-XXXX (Stainless stee	I cable with 6' Color cord.	200GLGUPC	Large Cast Guard	I with No Glass)	Textured Black	72	72M				
Replace XXXX w	ith color cord designation above) sh will match fixture finish.		ire Guard Finish will	match fixture finish.	Matte Black	73	73M				
**Cord/Cable Canopy fini	m Mounts				Textured Architectural Textured White	76 77	76M 77M				
	TC Flat Canony)				Textured Silver	78	78M				
Ste (Includes S	TC Flat Canopy) 3/4" (1" OD) Rigid Stems										
Ste (Includes S 1/2" (13/16" OD) Rigid 2ST6 2ST12 2ST18	3/4" (1" OD) Rigid Stems 3ST6 3ST12 3ST18							t charges and availa	ability.		
Ste (Includes S 1/2" (13/16" OD) Rigid	3/4" (1" OD) Rigid Stems	WARR	ΔΝΤΥ					t charges and availa	ability.		

© 2021 ANP Lighting. All rights reserved. These specifications are intended for general purposes only. ANP reserves the right to change material or design, without prior notice, in a continuing effort to upgrade its products.

Specifications VEC16

Fixture Type:

Customer:

Project:

Quantity:

			Customer:	
ARM MOUNTS Dimensi	ions are Projection x Height	CB included with all arms		GLASS & GUARDS UP TO 200W MAX
	F			CL = Clear FR = Frosted PR = Prismatic 100 = Small 200 = Large Glass Only 100 = 6 1/2" H X 4 1/8" W
E3 32" x 11 7/8"	E4 26" x 14"	E6 26" x 9 1/4"	E8 29 1/4" x 12 1/2"	200 = 9 1/4" H X 5" W 200GLCL 200GLFR
		$ \longrightarrow $	 	200GLPR 200GLPR Glass with Cast Guard
E9 28" x 40 5/8"	E10 52 1/4" x 18"	E11 35 1/4" x 17 1/4"	E12 37 3/8" x 2"	100 = 7 1/2" H X 4 1/8" W 200 = 10 1/4" H X 5 1/2" W
	\bigcap		⊨	200GLCLGUPC 200GLFRGUPC 200GLPRGUPC
				Glass with Wire Guard
E15 13 3/8" x 10 1/2"	E18 27 3/4" x 21 3/8"	E24 10" x 2"	E25 23" x 5 1/4"	100 = 7 1/2" H X 4 1/8" W 200 = 10 1/4" H X 5" W 200GLCLGUP 200GLFRGUP 200GLPRGUP
WALL MOUNTS Dimens	sions are Projection x Height	ions are Projection x Height	GUPC Guard Only	
			\bigcap	100 = 7 1/2" H X 4 1/8" W 200 = 10 1/4" H X 5" W 200GLGUPC (Cast Guard)
WM35 20 1/2" x 25"	WM41 10 1/2" x 14 3/4"	PM10 14 1/2" x 25"	PM20 30 1/8" x 25"	GUP Guard Only
WM55 20 5/8" x 14 1/4"	WM318 12" x 12 3/4"	PM30 21 5/8" x 28 7/8"	PM40 43 3/8" x 28 7/8"	100 = 7 1/2" H X 4 1/8" W 200 = 10 1/4" H X 5" W 200GLGUP (Wire Guard)
		PM50 27" x 38"	PM319 16 5/8" x 27 1/2"	
ACCESSORIES				
		\sim		
SBC	PC	<u>SC</u> ТВК	SLC	

© 2021 ANP Lighting. All rights reserved. These specifications are intended for general purposes only. ANP reserves the right to change material or design, without prior notice, in a continuing effort to upgrade its products.

ANPLighting **Specifications VEC16** Project: Fixture Type: Quantity: Customer: _ All fabric Color Cords are three conductor, 1/4" diameter Solid Fabric Colored Cords BLSF | Black CHSF | Chocolate Brown GYSF | Gray WHSF | White CASF | Cardinal ORSF | Orange LGSF | Lime Green KGSF | Kelly Green CBSF | Cobalt Blue SBSF | Sky Blue **Patterned Fabric Colored Cords** BWHPF | Black/White Houndstooth BIHPF | Houndstooth GYCPF | Gray/Citrus Yellow MOSPF | Magenta/Orange Stripe NMTPF | Navy Mini Tweed **Glossy Fabric Colored Cords** 01312021 GMGF | Gun Metal SSGF | Sterling Silver CPGF | Copper Penny BRGF | Bronze GOGF | Gold

© 2021 ANP Lighting. All rights reserved. These specifications are intended for general purposes only. ANP reserves the right to change material or design, without prior notice, in a continuing effort to upgrade its products.

1-800-548-3227 ANPlighting.com