

Specifications

Material:

Durable A356 cast aluminum and aluminum sheet metal. Hardware is stainless steel or zinc-plated steel.

Fixture Mounting:

Post Mount: Post Cap with set screws.

Drivers:

Universal Voltage 120-277V is standard. 0-10V dimming is standard. (Refer to Driver Specification section for other specifications.)

Dark Sky Friendly:

To maintain dark sky friendly compatibility: ≤ 3000K

Electrical:

A lightning surge protective device is standard (20KA³ Max/10KA² Nominal). Approximately 12" of pull wire extends from luminaire. All luminaires are prewired with 0-10V dimming leads. Post Arms and Wall Mounts are also prewired with line voltage & dimming leads.

Finish:

A polyester powder coat high quality finish. Marine grade finish is available.

Certifications:

UL Listed for outdoor, wet location. LED is IP66.

Modifications:

Consult factory for custom or modified designs.

Buy American:

This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

LA790 LED

EPA: 0.65

Weight: 13 lbs.

Catalog Logic

LA790	1	AM20W	D	40K	-	PC	-	PA5651	-	72
Luminaire Series	Fixture Orientation	Light Source & Wattage	Optics	CCT	Accessories	Mounting Source	Finish			

Catalog Number

1

2

3

4

5

6

7

8

LA790

1

1 FIXTURE ORIENTATION

1 (Post)

2 LIGHT SOURCE & WATTAGES

ANP Module

AM10W (10W ANP Module COB)

AM20W (20W ANP Module COB)

AM30W (30W ANP Module COB)

AM40W (40W ANP Module COB)

3 OPTICS

D (Type V : Frosted Acrylic Dome)

4 CCT (COLOR TEMPERATURE)

27K (2700K)

30K (3000K)

35K (3500K)

40K (4000K)

*Consult Factory for 5000K

5 ACCESSORIES

HSS90 (90° House Side Shield)

HSS120 (120° House Side Shield)

*EMG-LED10 (10W LED Emergency Driver, See Below For Compatibility)

*EMG-LED20 (20W LED Emergency Driver, See Below For Compatibility)

HLMSPC-06 (On/Off Motion Sensor/Photocell, High/Low field-configurable; 15' - 30' Sensor Mounting Height)

HLMSPC-10 (On/Off Motion Sensor/Photocell, High/Low field-configurable; 8' - 15' Sensor Mounting Height)

PC (Button Photo Cell)

TLPC (ANSI C136.41 Twist Lock Photocell, includes receptacle and 120-277V photo cell)

TL5 (ANSI C136.41 5-Pin Twist Lock Receptacle only)

TL7 (ANSI C136.41 7-Pin Twist Lock Receptacle only)

FAID (Field Adjustable Internal Dimmer)

*Most Emergency Drivers are remote mount only (consult factory). 10W & 30W Emergency Drivers are not compatible with all LED Light Source and Wattages. For percent lumens in emergency mode, see [Technical Section](#)

6 MOUNTING SOURCE

Post Mount Options

S3 (Slips over Ø3" pole or tenon)

S4 (Slips over Ø4" pole or tenon)

S5 (Slips over Ø5" pole or tenon)

TN3 (Mounts to Ø3" pole with Ø2-3/8" x 4" tenon)

TN4 (Mounts to Ø4" pole with Ø2-3/8" x 4" tenon)

TN5 (Mounts to Ø5" pole with Ø2-3/8" x 4" tenon)

OM (Other Mounting, Please Specify)

PA3111

PA3113

PA5151

PA5153

PA5411

PA5413

PA8521

WM4511

WM4513

WM5133

WM5161

WM5163

WM5601

WM5603

All Poles

All Post Mounts

All Wall Mounts

Post Mount Arms

PA3111

PA3113

PA5151

PA5153

PA5411

PA5413

PA8521

WM4511

WM4513

WM5133

WM5161

WM5163

WM5601

WM5603

All Poles

All Post Mounts

All Wall Mounts

All Poles

All Post Mounts

All Wall Mounts

All Poles

All Post Mounts

All Wall Mounts

All Poles

All Post Mounts

All Wall Mounts

All Poles

All Post Mounts

All Wall Mounts

All Poles

All Post Mounts

All Wall Mounts

All Poles

All Post Mounts

All Wall Mounts

All Poles

All Post Mounts

All Wall Mounts

7 FINISHES

*Premium and Marine Grade Finish have additional charges

Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*
Aspen Green	10	10M	Copper Clay	53	53M
Cantaloupe	11	11M	Silver	56	56M
Lilac	12	12M	Black Verde	61	61M
Putty	13	13M	Painted Chrome	70	70M
Raw Unfinished	40	NA	Painted Copper	71	71M
Black	41	41M	Textured Black	72	72M
Forest Green	42	42M	Matte Black	73	73M
Bright Red	43	43M	Textured Architectural Bronze	76	76M
White	44	44M	Textured White	77	77M
Bright Blue	45	45M	Textured Silver	78	78M
Sunny Yellow	46	46M	PREMIUM FINISH	PREMIUM Grade*	Marine Grade*
Aqua Green	47	47M	Textured Desert	80	80M
Galvanized	49	NA	Graystone	82	82M
Navy	50	50M	Oil Rubbed Bronze	83	83M
Architectural Bronze	51	51M	Carbon Graphite	96	96M
Patina Verde	52	52M			

Consult Factory for additional paint charges and availability.

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

PERFORMANCE TABLE - ANP MODULE - DELIVERED LUMENS

			2700K					3000K					3500K					4000K				
LED CATALOG	WATTS	DISTRIBUTION	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G
AM10W	10W	TYPE V	352	35	0	0	0	370	37	0	0	0	374	37	0	0	0	379	38	0	0	0
AM20W	20W	TYPE V	705	35	1	0	0	739	37	1	0	0	748	37	1	0	0	757	38	1	0	0
AM30W	30W	TYPE V	1057	35	1	0	0	1109	37	1	0	0	1123	37	1	0	0	1136	38	1	0	0
AM40W	40W	TYPE V	1410	35	1	0	0	1479	37	1	0	0	1497	37	1	0	0	1514	38	1	0	0

MODULE SPECIFICATION

- CREE XLAMP™ CMU
- Typical Efficacy 90 lm/W
- CCT: 2700K, 3000K, 3500K, 4000K
- CRI: >90
- 3-Step Ellipse
- Ingress Protection: IP66
- Certifications: UL Recognized, RoHS, ENEC

DRIVER SPECIFICATION

- Universal Input: 120-277V
- Dimming: 0-10V, TRIAC, ELV (Dims to 1%)
- Power Factor @ Full Load >90%
- THD @ Full Load <20%
- Constant Current Output 50/60Hz
- Operating Temperature: -30°C Minimum
- Lifetime: >50,000 hours
- Ingress Protection: IP66
- Certifications: UL Recognized, CE

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray and is available in either a textured or gloss surface. 5-year warranty for aluminum products. 2-year warranty for steel products.

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

LED warranty information

- 5 year limited warranty*
- *Limited Warranty: A typical year is defined as 4,380 hours of operation.

ACCESSORIES



HSS90 & HSS120



EMG-LED10, 20




HLMSPC-06 & HLMSPC-10



PC



TLPC



TL5 & TL7



FAID

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

POPULAR POST MOUNTS

See Post Arm Section on Website for Specification Sheets and additional post arms. Dimensions are Projection x Height.
[Click here for all Post Mount styles](#)

PA3321 / 18" x 14 3/4"



PA5151 / 14 1/4" x 19 3/4"



PA5411 / 17 7/8" x 25 1/8"



PA5611 / 18 5/8" x 26 1/2"



PA5621 / 19" x 26 1/4"



PA5651 / 20" x 26 1/4"



PA6211 / 22 3/4" x 26 1/2"




PA6311 / 17" x 23 1/4"



PA7911 / 20" x 20 5/8"



PA8031 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8571 / 24" x 47"

POPULAR WALL MOUNTS

See Wall Mount Section on Website for Specification Sheets and additional wall mount arms. Dimensions are Projections x Height.
[Click here for all Wall Mount styles](#)

WM2141 / 18" x 12 3/16"




WM2211 / 15 1/2" x 15 7/8"



WM3001 / 11" x 8 7/8"



WM3351 / 14 1/2" x 17"



WM4511 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5161 / 15 3/4" x 17 3/4"



WM5311 / 10 7/8" x 10"



WM5601 / 17 7/8" x 14"



WM5611 / 17 5/8" x 22"



WM7421 / 16 3/8" x 15 3/4"



WM8021 / 19 1/4" x 16 3/8"

COLUMN MOUNT



CM / 5 3/4" SQ x 3 1/2" H

FINISHES COLORS

STANDARD



PREMIUM

