



Aluminum Product

This limited warranty is provided by ANP Lighting, ("Seller") to original purchaser ("Buyer") as described below and extends to the finish for aluminum lighting products. ANP Lighting warrants our standard high-quality finishes are processed and treated to create a lasting protection, when delivered in new condition and in its original packaging, will be free of cracking, peeling, excessive fading, and corrosion defects for a period of five (5) years from the date of shipment.

Aluminum Marine Grade Option

ANP Lighting does not warrant paint and material finishes when Product(s) is installed in a salt air coastal application unless the product(s) is ordered with Optional Marine Grade Powder Coat Finish. If marine grade powder coat finish is chosen the standard warranty will be five (5) years from date of shipment. All other conditions remain the same from the above limited warranty.

Steel Product

This limited warranty is provided by ANP Lighting, ("Seller") to original purchaser ("Buyer") as described below and extends to the finish for steel lighting products. ANP Lighting warrants our standard high-quality finishes are processed and treated to create a lasting protection, when delivered in new condition and in its original packaging, will be free of cracking, peeling, excessive fading, and corrosion defects for a period of two (2) years from the date of shipment.

Steel Marine Grade Option

ANP Lighting does not warrant paint and material finishes when Product(s) is installed in a salt air coastal application unless the product(s) is ordered with Optional Marine Grade Powder Coat Finish. If marine grade powder coat finish is chosen the standard warranty will be two (2) years from date of shipment. All other conditions remain the same from the above limited warranty.

There is no rust or corrosion warranty if products are ordered Raw/unpainted.

ANP does not warranty for items damaged by nicks, cuts, scratches or any other normal wear and tear on the item as it is being used.

The following acts and/or omissions will void the warranty:

- Physical damage due to transport or installation
- Contact with salt water, magnesium chlorides, ice melt
- Contact with chlorine, fertilizer pesticides, or industrial chemical agents
- Contact with sprinkler systems, tree sap, entangled vegetation or normal wear and tear.
- Alteration of coating by owner or agents of owner
- Physical damage due to natural disasters

Mechanical and Physical Properties

ADHESION	Crosshatch adhesion using .0625" squares; no failure
PENCIL HARDNESS	2H minimum
IMPACT TEST	150 inch pounds direct 150 inch pounds reverse
GLOSS	50% retention
SALT FOG TESTING	2,500+ hours in a 5% solution at 95-degrees F and 95% humidity with no creepage (ASTM B-117)
HUMIDITY	1,000 hours at 110-degrees F and 100% relative humidity
WEATHERING	95% gloss retention under a sun simulator for 1,000 hours