

Specifications

Material:
Durable A356 cast aluminum and aluminum sheet metal. Hardware is stainless steel or zinc-plated steel.

Fixture Mounting:
Post Mount: Post Cap with set screws.

Drivers:
Universal Voltage 120-277V is standard. 0-10V dimming is standard. (Refer to Driver Specification section for other specifications.)

Dark Sky Friendly:
To maintain dark sky friendly compatibility: ≤ 3000K

Electrical:
A lightning surge protective device is standard (20KA³ Max/10KA² Nominal). Approximately 12" of pull wire extends from luminaire. All luminaires are prewired with 0-10V dimming leads. Post Arms and Wall Mounts are also prewired with line voltage & dimming leads.

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

Finish:
A polyester powder coat high quality finish. Marine grade finish is available.

Certifications:
UL Listed for outdoor, wet location. LED is IP66.

Modifications:
Consult factory for custom or modified designs.

Buy American:
This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

LA790 LED

EPA: 0.65
Weight: 13 lbs.

Catalog Logic						
LA790	1	AM20W	T5	40K	PC	PA5651 - 72
Luminaire Series	Fixture Orientation	Light Source & Wattage	Optics	CCT	Accessories	Mounting Source

Catalog Number								
1	2	3	4	5	6	7	8	
LA790	1							

1	FIXTURE ORIENTATION
1 (Post)	

2	LIGHT SOURCE & WATTAGES
ANP Module	
AM10W (10W ANP Module COB)	
AM20W (20W ANP Module COB)	
AM30W (30W ANP Module COB)	
AM40W (40W ANP Module COB)	

3	OPTICS
T5 (Type V)	

4	CCT (COLOR TEMPERATURE)
27K (2700K)	
30K (3000K)	
35K (3500K)	
40K (4000K)	
*Consult Factory for 5000K	

5	ACCESSORIES
HSS90 (90° House Side Shield)	
HSS120 (120° House Side Shield)	
*EMG-LED10 (10W LED Emergency Driver, See Below For Compatibility)	
*EMG-LED20 (20W LED Emergency Driver, See Below For Compatibility)	
HLMSPC-06 (On/Off Motion Sensor/Photocell, High/Low field-configurable; 15' - 30' Sensor Mounting Height)	
HLMSPC-10 (On/Off Motion Sensor/Photocell, High/Low field-configurable; 8' - 15' Sensor Mounting Height)	
PC (Button Photo Cell)	
TLPC (ANSI C136.41 Twist Lock Photocell, includes receptacle and 120-277V photo cell)	
TL5 (ANSI C136.41 5-Pin Twist Lock Receptacle only)	
TL7 (ANSI C136.41 7-Pin Twist Lock Receptacle only)	
FAID (Field Adjustable Internal Dimmer)	
*Most Emergency Drivers are remote mount only (consult factory). 10W & 30W Emergency Drivers are not compatible with all LED Light Source and Wattages. For percent lumens in emergency mode, see Technical Section	

6	MOUNTING SOURCE																														
<table border="1"> <thead> <tr> <th>Post Mount Options</th> <th>Post Mount Arms</th> <th>Wall Mount Arms</th> </tr> </thead> <tbody> <tr> <td>S3 (Slips over Ø3" pole or tenon)</td> <td>PA3111</td> <td>WM4511</td> </tr> <tr> <td>S4 (Slips over Ø4" pole or tenon)</td> <td>PA3113</td> <td>WM4513</td> </tr> <tr> <td>S5 (Slips over Ø5" pole or tenon)</td> <td>PA5151</td> <td>WM5133</td> </tr> <tr> <td>TN3 (Mounts to Ø3" pole with Ø2-3/8" x 4" tenon)</td> <td>PA5153</td> <td>WM5161</td> </tr> <tr> <td>TN4 (Mounts to Ø4" pole with Ø2-3/8" x 4" tenon)</td> <td>PA5411</td> <td>WM5163</td> </tr> <tr> <td>TN5 (Mounts to Ø5" pole with Ø2-3/8" x 4" tenon)</td> <td>PA5413</td> <td>WM5601</td> </tr> <tr> <td>OM (Other Mounting, Please Specify)</td> <td>PA8521</td> <td>WM5603</td> </tr> <tr> <td colspan="2">All Poles</td> <td>All Post Mounts</td> </tr> <tr> <td colspan="3">All Wall Mounts</td> </tr> </tbody> </table>		Post Mount Options	Post Mount Arms	Wall Mount Arms	S3 (Slips over Ø3" pole or tenon)	PA3111	WM4511	S4 (Slips over Ø4" pole or tenon)	PA3113	WM4513	S5 (Slips over Ø5" pole or tenon)	PA5151	WM5133	TN3 (Mounts to Ø3" pole with Ø2-3/8" x 4" tenon)	PA5153	WM5161	TN4 (Mounts to Ø4" pole with Ø2-3/8" x 4" tenon)	PA5411	WM5163	TN5 (Mounts to Ø5" pole with Ø2-3/8" x 4" tenon)	PA5413	WM5601	OM (Other Mounting, Please Specify)	PA8521	WM5603	All Poles		All Post Mounts	All Wall Mounts		
Post Mount Options	Post Mount Arms	Wall Mount Arms																													
S3 (Slips over Ø3" pole or tenon)	PA3111	WM4511																													
S4 (Slips over Ø4" pole or tenon)	PA3113	WM4513																													
S5 (Slips over Ø5" pole or tenon)	PA5151	WM5133																													
TN3 (Mounts to Ø3" pole with Ø2-3/8" x 4" tenon)	PA5153	WM5161																													
TN4 (Mounts to Ø4" pole with Ø2-3/8" x 4" tenon)	PA5411	WM5163																													
TN5 (Mounts to Ø5" pole with Ø2-3/8" x 4" tenon)	PA5413	WM5601																													
OM (Other Mounting, Please Specify)	PA8521	WM5603																													
All Poles		All Post Mounts																													
All Wall Mounts																															
<table border="1"> <thead> <tr> <th>Column Mount</th> </tr> </thead> <tbody> <tr> <td>CM Column Mount</td> </tr> </tbody> </table>		Column Mount	CM Column Mount																												
Column Mount																															
CM Column Mount																															
See last page for popular mounting sizes/styles.																															

7	FINISHES					
*Premium and Marine Grade Finish have additional charges						
Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*	Marine Grade*
Aspen Green	10	10M	Copper Clay	53	53M	
Cantaloupe	11	11M	Silver	56	56M	
Lilac	12	12M	Black Verde	61	61M	
Putty	13	13M	Painted Chrome	70	70M	
Raw Unfinished	40	NA	Painted Copper	71	71M	
Black	41	41M	Textured Black	72	72M	
Forest Green	42	42M	Matte Black	73	73M	
Bright Red	43	43M	Textured Architectural Bronze	76	76M	
White	44	44M	Textured White	77	77M	
Bright Blue	45	45M	Textured Silver	78	78M	
Sunny Yellow	46	46M	PREMIUM FINISH	Premium Grade*	Marine Grade*	
Aqua Green	47	47M	Textured Desert	80	80M	
Galvanized	49	NA	Graystone	82	82M	
Navy	50	50M	Oil Rubbed Bronze	83	83M	
Architectural Bronze	51	51M	Carbon Graphite	96	96M	
Patina Verde	52	52M				

Consult Factory for additional paint charges and availability.

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

PERFORMANCE TABLE - ANP MODULE - DELIVERED LUMENS

LED CATALOG	WATTS	DISTRIBUTION	2700K				3000K				3500K				4000K							
			DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G
AM10W	10W	TYPE V	352	35	0	0	0	370	37	0	0	0	374	37	0	0	0	379	38	0	0	0
AM20W	20W	TYPE V	705	35	1	0	0	739	37	1	0	0	748	37	1	0	0	757	38	1	0	0
AM30W	30W	TYPE V	1057	35	1	0	0	1109	37	1	0	0	1123	37	1	0	0	1136	38	1	0	0
AM40W	40W	TYPE V	1410	35	1	0	0	1479	37	1	0	0	1497	37	1	0	0	1514	38	1	0	0

MODULE SPECIFICATION

- Citizen CLU03Q COB LED
- Typical Efficacy 90 lm/W
- CCT: 2700K, 3000K, 3500K, 4000K
- CRI: >90
- 2-Step Ellipse
- Ingress Protection: IP66
- Certifications: UL Recognized, RoHS, ENEC

DRIVER SPECIFICATION

- Universal Input: 120-277V
- Dimming: 0-10V, TRIAC, ELV (Dims to 1%)
- Power Factor @ Full Load >90%
- THD @ Full Load <20%
- Constant Current Output 50/60Hz
- Operating Temperature: -30°C Minimum
- Lifetime: >50,000 hours
- Ingress Protection: IP66
- Certifications: UL Recognized, CE

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray and is available in either a textured or gloss surface. 5-year warranty for aluminum products. 2-year warranty for steel products.

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

LED warranty information

- 5 year limited warranty*
- *Limited Warranty: A typical year is defined as 4,380 hours of operation.

ACCESSORIES



HSS90 & HSS120



EMG-LED10, 20



HLMSPC-06 & HLMSPC-10



PC



TLPC



TL5 & TL7



FAID

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

POPULAR POST MOUNTS

See Post Arm Section on Website for Specification Sheets and additional post arms. Dimensions are Projection x Height.
[Click here for all Post Mount styles](#)



PA3321 / 18" x 14 3/4"



PA5151 / 14 1/4" x 19 3/4"



PA5411 / 17 7/8" x 25 1/8"



PA5611 / 18 5/8" x 26 1/2"



PA5621 / 19" x 26 1/4"



PA5651 / 20" x 26 1/4"



PA6211 / 22 3/4" x 26 1/2"



PA6311 / 17" x 23 1/4"



PA7911 / 20" x 20 5/8"



PA8031 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8571 / 24" x 47"

POPULAR WALL MOUNTS

See Wall Mount Section on Website for Specification Sheets and additional wall mount arms. Dimensions are Projections x Height.
[Click here for all Wall Mount styles](#)



WM2141 / 18" x 12 3/16"




WM2211 / 15 1/2" x 15 7/8"



WM3001 / 11" x 8 7/8"



WM3351 / 14 1/2" x 17"



WM4511 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5161 / 15 3/4" x 17 3/4"



WM5311 / 10 7/8" x 10"



WM5601 / 17 7/8" x 14"



WM5611 / 17 5/8" x 22"



WM7421 / 16 3/8" x 15 3/4"



WM8021 / 19 1/4" x 16 3/8"

COLUMN MOUNT



CM / 5 3/4" SQ x 3 1/2" H

FINISHES COLORS

STANDARD



PREMIUM

